

## Eaton Industrial Hose EH920 - UL LPG



# Overview & Features

---

Transfer and delivery of propane, butane and natural gas in well ventilated areas ( 1 psiG maximum working pressure)

### Features

- 350 psi operating pressure
- -40 F to 140 F
- Cover: Pin-pricked vinyl Neoprene
- Textile braid reinforcement with stainless steel anti-static wire
- Tube: Nitrile
- 5:1 safety factor
- Meets UL 21

# Where Used

---



### Buildings

**Applications:**


- Transfer of Natural Gas, Propane and Butane



### Marine

**Applications:**

- Transfer of Natural Gas, Propane and Butane




### Mining, metals and minerals

**Platforms:**

- Steel Mill Furnaces

**Applications:**

- Transfer of Natural Gas, Propane and Butane



### Oil and gas

**Platforms:**

- Downstream: Petrochemical
- Downstream: Refining (Ethanol/ Biodiesel)
- Downstream: Terminal Operations (refined gas and liquids)
- Liquefied Natural Gas/ Compressed Natural Gas
- Midstream: Terminal Operations (unrefined gas and liquids)
- Upstream: Onshore Drilling Operations

**Applications:**

- Transfer of Natural Gas, Propane and Butane



### Rail

**Applications:**

- Transfer of Natural Gas, Propane and Butane



### Vehicles

**Platforms:**

- Pick-Up and Delivery (LTL)

**Applications:**

- Transfer of Natural Gas, Propane and Butane

# Value Propositions

---

★ = Denotes point of differentiation

Value Proposition Statement	Audiences		
	OEM	Distributor	End User
Completes breadth of portfolio to capitalize on core product market opportunities			
Easy identification in the toughest environments provided by dual Mylar and embossed laylines , verses competitive single layline alternatives, creating ease of replenishment and traceability			

## Tools & Collateral

---

### Brochure

[Industrial Hose Oil and Gas Exploration](#)

### Catalog

[Industrial Hose Catalog North America : E-HOOV-MC003-E2](#)