

Eaton Industrial Hose EH920 - UL LPG



Overview & Features

Transfer and delivery of propane, butane and natural gas in well ventilated areas (1 psiG maximum working pressure)

Features

- 350 psi operating pressure
- -40 F to 140 F
- Cover: Pin-pricked vinyl Neoprene
- Textile braid reinforcement with stainless steel anti-static wire
- Tube: Nitrile
- 5:1 safety factor
- Meets UL 21

Where Used



Buildings

Applications:


- Transfer of Natural Gas, Propane and Butane



Marine

Applications:

- Transfer of Natural Gas, Propane and Butane




Mining, metals and minerals

Platforms:

- Steel Mill Furnaces

Applications:

- Transfer of Natural Gas, Propane and Butane



Oil and gas

Platforms:

- Downstream: Petrochemical
- Downstream: Refining (Ethanol/ Biodiesel)
- Downstream: Terminal Operations (refined gas and liquids)
- Liquefied Natural Gas/ Compressed Natural Gas
- Midstream: Terminal Operations (unrefined gas and liquids)
- Upstream: Onshore Drilling Operations

Applications:

- Transfer of Natural Gas, Propane and Butane



Rail

Applications:

- Transfer of Natural Gas, Propane and Butane



Vehicles

Platforms:

- Pick-Up and Delivery (LTL)

Applications:

- Transfer of Natural Gas, Propane and Butane

Value Propositions

★ = Denotes point of differentiation

Value Proposition Statement	Audiences		
	OEM	Distributor	End User
Completes breadth of portfolio to capitalize on core product market opportunities			
Easy identification in the toughest environments provided by dual Mylar and embossed laylines , verses competitive single layline alternatives, creating ease of replenishment and traceability			

Tools & Collateral

Brochure

[Industrial Hose Oil and Gas Exploration](#)

Catalog

[Industrial Hose Catalog North America : E-HOOV-MC003-E2](#)